



KTMED INC.
medical systems

ANGELUS

Vital Sign Monitor



ANGELUS – Proven performance with our advanced technology – is ideal for bedside, transport and ambulatory procedure. ANGELUS monitors two parameters, SpO2 and blood pressure, accurately. It is easy to use and handy to transport the device from patient to the other.

Product Highlights

- Easy-to-Use, accurate and reliable
- Rugged, Portable, Light weight
- Large LED displays, Easy-to-Read
- Suitable for both Adult and Pediatric





Technical Specifications

ANGELUS

SpO₂ %	Measuring range	0-100%	
	Accuracy	± 1% (90-100%)	
		± 2% (80-89%)	
		± 3% (65-79%)	
		Unspecified (below 64%)	
Pulse	Measuring range	25-255bpm	
	Accuracy	± 1%	
NIBP	Measuring range	Adult	30-300mmHg
		Neonate	15-150mmHg
	Accuracy	± 3mmHg or 2%	
	Maximum pressure	Adult	300mmHg
Neonate		150mmHg	
Indicator	Indicator	3 Digit Dual Color FND 4EA (SpO ₂ , HR, NIBP)	
		4 Digit FND (Time)	
		10-BAR LED 1EA (Amplitude)	
Trend	48hours		
Alarm	SpO ₂ , HR, NIBP (Sys., Dia., MAP)		
Power	External power	AC100-240V, 50/60Hz	
	Batteries	Rechargeable battery 1.2VX6ea, 2.5AH	
	Battery running time	2.5hours	
	FUSE	240V 2A X2ea	
General Condition	Max. consumption power	25VA	
	Dimension	200(W)X170(H)X100(D)mm	
	Weight	1.3kg	
	Operating temperature	0 to +50°C	
	Storage temperature	-20°C to +60°C	
	Humidity	10% - 95% (non-condensing)	
Safety classification	ANGELUS	Class IIb	
		BF APPLIED PART	

Warranty : 2years for main unit, 1year for sensor



KTMED INC.
medical systems

#811, Hanshin IT Tower, 235 Guro-3dong, Guro-gu, Seoul, Korea
Tel : +82-2-2108-7890 Fax : +82-2-2108-7894
Website : www.ktmed.com E-mail : master@ktmed.com

